

**WHP 30 HKX**  
**MOTOPOMPA DE PRESIUNE****MOTOR**

Tip:  
Model:  
Putere maximă [CP]:  
Diametru piston x cursă:  
Capacitate cilindrică:  
Compresie:  
Combustibil:  
Filtru de aer:  
Senzor lipsa ulei:  
Capacitate rezervor:  
Consum:  
Pornire:

**HONDA**

OHV, 4 timpi, racire cu aer  
GX 270  
9  
77 x 58 mm  
270 cm<sup>3</sup>  
8,5 : 1  
benzina fara plumb  
dual  
da  
5.3 l  
2.0 l/h la 3600 rpm  
demaror mecanic

**CARACTERISTICI TEHNICE POMPA**

Diametru de aspiratie: 3"  
Diametru de refulare: 2"1/2 + 2 x 1"1/2  
Inaltimea maxima de refulare: 75,0 m  
Adancimea maxima de aspiratie: 7m  
Debit maxim: 44 m<sup>3</sup>/h (730 l/min)  
Diametru maxim corpuri solide: 4 mm  
Garnitura mecanica: SiC (carbura de siliciu)  
Sistem pornire: demaror mecanic  
Masa: 45 kg  
Dimensiuni de gabarit: 585x485x540 mm



**Dotare standard:**

- stuturi aspiratie si refulare din aluminiu
- piulite aspiratie si refulare din aluminiu
- garnituri aspiratie si refulare
- sorb 3"
- coliere pentru furtun
- dopuri pentru refulare

